

Large Studded Anti-Slip Matting Datasheet


Product Code: RC04167

Product Description

Our flexi coin flooring is a large studded anti-slip matting solution. We manufacture this product from a high quality PVC due to the excellent versatility, as well as safety, that the material offers. The coin pattern on the surface of the rolls make our large studded matting stand out against similar products due to the extra grip it provides.

Size Specifications

Stock Sizes	Thickness	Weight (Kg/m ²)
25m x 0.98m	1.6mm	2.37
25m x 1.5m	1.6mm	2.37



Technical Specification

Properties	Data
Product	Large Studded Anti Slip Matting
Composition	Flexible Polyvinyl Chloride (PVC)
Chemical Resistance	Resistant to most acids, alkalines and oils
Fire Resistance	EN 13501-1: 2007-Bfl-S1
Temperature Range	-23°C to +60°C
UV Resistance	Resistant to PVC degradation
Reversion	Thermoplastic shrinkage can result in size reductions up to 2%
Environment	100% recyclable

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. RubberSmart cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

The smart way to buy rubber & plastics

Matting Colour Options



Other colours available as a special order, subject to minimum order quantities

Matting Installation

As we supply our Large Studded PVC matting in a single roll, installation is quick and simple.

- Loose lay, no permanent fixtures required
- Supplied in 25m rolls, simply cut to size
- Holes can be cut to accommodate objects
- Contours to the floor surface

Cleaning & Maintenance

Keeping our Large Studded PVC matting clean is a quick and easy job.

- Simply lift or roll matting to clean
- Easy to clean with a vacuum or mop
- No special cleaning tools required

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. RubberSmart cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.