

## Anti Static Neoprene Sheeting BS490 & ISO340

Product Code: RC0330

### Key Features

Our anti static neoprene sheeting is a high quality and highly versatile material. This particular grade fully confirms to BS 490 and ISO 340 specifications for anti static and flame retardant properties. This combination of properties enables you to use our sheeting in a wide range of transportation, construction as well as manufacturing industries.

### Size Specifications

#### Standard Thicknesses

1.0mm, 1.5mm, 2.0mm, 3.0mm, 4.0mm, 5.0mm, 6.0mm, 10.0mm, 12.0mm, 15.0mm, 20.0mm, 25.0mm

### Technical Specification

| Properties                                              | Values                                 |
|---------------------------------------------------------|----------------------------------------|
| Product                                                 | Anti-Static & Flame Retardant Sheeting |
| Compound                                                | CR/SBR                                 |
| Hardness (Shore A)                                      | 60° ± 5°                               |
| Density                                                 | 1.20 g/cm <sup>2</sup>                 |
| Tensile Strength                                        | 80 Kg/cm <sup>2</sup>                  |
| Elongation at Break                                     | 250%                                   |
| Compression Set (22h, 70°C)                             | 25%                                    |
| Working Temperature Range                               | -30°C to + 100°C                       |
| <b>Flame Resistance (according to ISO 340)</b>          |                                        |
| Flame persistence (After Removing the Burner)           | Max 45s                                |
| <b>Anti-static Characteristic (according to BS 490)</b> |                                        |
| Surface Electrical Resistance                           | 3 x 10 <sup>8</sup> Ω (Max)            |

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. RubberSmart cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.



#### Available In -



Full Rolls



Cut to strip



Bespoke  
Gaskets