

CloseGrip Non-Slip Matting Datasheet

Product Code: RC04122

Key Features

- Excellent grip in all weather conditions
- Close grid design ideal for wheeled traffic
- Self-draining
- Resistant to chemicals, acids, and oils
- Easy to install
- Contours to uneven surfaces
- Minimal maintenance required

Size Specifications

Stock Size	Thickness	Weight
10m x 0.6m	14mm	10.5kg/m ²
10m x 0.91m	14mm	10.5kg/m ²
10m x 1.22m	14mm	10.5kg/m ²



**ISO
9001 : 2015**
REGISTERED

Technical Specification

Property	Value
Product	Non-slip matting
Composition	Flexible polyvinyl chloride (PVC)
Acoustic Insulation	Excellent sound absorption properties
Chemical Resistance	Resistant to most acids, alkalines, and oils
Fire Resistance	EN ISO 13501 - 1 : 2007 - Cfl - S1
Slip Resistance	DIN 51130: R11, V10 ASTM E303 Dry/Wet with lines along/lines across 72-93/57-79
Temperature Range	-23°C to +60°C
UV Resistance	Resistant to PVC degradation
Reversion	Thermoplastic shrinkage can result in size reductions up to 2%
Hygiene	Naturally resistant to bacteria growth
Environmental	100% recyclable

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. RubberSmart cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.