

## HARDI Fuel Pump 1112-1 12V

Product Code: RC-CC-HFP1112-1

### Key Features

- Works independent of the engine
- Easy fitting
- Self-priming
- Delivery is adapted to consumption of the engine
- Supports unleaded petrol, diesel, and methanol and ethanol fuels
- Dual polarity
- Suitable for a large range of classic car makes and models



### Compatible Vehicles

| Make         | Model             | Year                     |
|--------------|-------------------|--------------------------|
| Alvis        | All               | 1950                     |
| Aston Martin | 4-Cylinder        | 1950                     |
| Lea-Francis  | All               | Up to and including 1950 |
| MG           | All               | Up to and including 1957 |
| MG           | Midget MkIII      | 1967                     |
| Morris       | All               | Up to and including 1957 |
| Morris       | Minor             | 1957 to 1959             |
| Riley        | RMB / RMC         | 1948 to 1951             |
| Riley        | 4-Cylinder Export | 1952                     |
| Riley        | RMA               | 1955                     |
| Singer       | All               |                          |
| Wolseley     | All               | Up to and including 1953 |
| Wolseley     | 4/44              | 1954 to 1956             |
| Wolseley     | 1500              | 1959 to 1964             |
| Wolseley     | Hornet            | 1965 to 1966             |
| Wolseley     | 1100              | 1960 to 1965             |

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. RubberSmart or The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

The smart way to buy rubber & plastics

## Technical Data

| Property           | Value           |
|--------------------|-----------------|
| Conveying Capacity | 60 - 80 l/h     |
| Pressure           | 0.13 - 0.20 bar |
| Starting Voltage   | 9.0 - 9.5 V     |
| Operating Voltage  | 12 V            |
| Power Consumption  | 1.5 - 1.9 A     |
| Suction Head       | <1.5 m          |
| Weight             | 900 g           |
| Cold Resistance    | Down to -40° C  |
| Heat Resistance    | Up to +80° C    |

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. RubberSmart or The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

**E** [info@rubbersmart.co.uk](mailto:info@rubbersmart.co.uk)

**W** [www.rubbersmart.co.uk](http://www.rubbersmart.co.uk)

**T** +44 (0) 1794 328 412

RubberSmart is a trading name of The Rubber Company Limited - Registered in England and Wales  
Company Number - 08350831 | VAT Number - GB 156 8355 80

