

Anti-Slip Safety Grip Tape - Hazard

Product Code: RC3401-HAZ

Key Features

- High-performance anti-slip protection for internal and external use
- Fire tested according to ECE R-118.03, Annex 6, 7, and 8
- Pendulum tested to BS 7976:2
- Good resistance to chemicals and contaminants
- Strong self-adhesive backing adheres to most surfaces
- Suitable for commercial, industrial and domestic applications

Attributes



Anti-Slip



Durable



Flame Retardant



Technical Data

Property	Test Method	Value
Back Carrier	Calipers	0.1mm PVC
Total Applied Thickness	Calipers	0.7mm
Type of Adhesive	-	Solvent Acrylic
Mineral Type	-	Aluminium Oxide
Adhesion to Steel	PSTC-4	1500 g/25.4mm ²
Tensile Strength	PSTC-31 Lloyd, 500N Load Cell	6.0 kg/25.4mm ² 68.0 N/25mm
Tear Resistance	PSTC-39	5600 g ± 200g
Elongation at Break	PSTC-31	25 %
Peel Adhesion (20 m dwell)	180° FINAT FTMI	23.5 N/25mm
Peel Adhesion (24 h dwell)	180° FINAT FTMI	27.2 N/25mm
Temperature Range	-	-40°C to +70°C
Resistance to Water	PSTC-35	10 Months

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. RubberSmart or The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

The smart way to buy rubber & plastics

Technical Data Continued

Property	Test Method	Value
Resistance to Chemicals	PSTC-35	8 Months
Resistance to Motor Oil	PSTC-35	Excellent
Life Span	PSTC-9	12 to 24 Months
Maximum Size of Roll Production	-	1168mm x 100m
Coefficient of Friction - Dry Surface	Pendulum EN 13036-4	102 TRL
Coefficient of Friction - Wet Surface	Pendulum EN 13036-4	71 TRL

Light Reflective Values

Colour	RAL	Average LRV	Range
Black	9017	0	0
Yellow	1023	37.5	3
Red	3020	4	0
White	9003	72	2

Approvals



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. RubberSmart or The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

E info@rubbersmart.co.uk**W** www.rubbersmart.co.uk**T** +44 (0) 1794 328 412

RubberSmart is a trading name of The Rubber Company Limited - Registered in England and Wales
Company Number - 08350831 | VAT Number - GB 156 8355 80

